



<b>DESCRIPTION:</b>	22 AWG 8 conductor <u>plenum</u> communications cable Nom. O.D. (in.) 0.25
<b>CONSTRUCTION:</b>	Conductors: 22 AWG 7 strand bare copper
<b>Insulation:</b>	0.0063" nominal wall Complex Plenum PVC .0415
<b>Core Assembly:</b>	8 conductors are cabled to a 2.5" L.H.L. and jacketed
<b>Jacket:</b>	0.014" nominal wall White Complex Plenum PVC .165 Parallel ripcord located under jacket
<b>COLOR CODE:</b>	Black, White, Red, Green, Brown, Blue, Orange, Yellow
<b>SPECIFICATIONS:</b>	UL 13, Power Limited Circuit Cable UL 1424 Power Limited Fire Alarm Cable UL 444, Communication Cables NFPA 262, Plenum Flame Test (UL 910) NEC Article 725, 760 and 800
<b>CERTIFICATIONS:</b>	UL Listed Type CL3P/FPLP UL and cUL Listed Type CMP California State Fire Marshal Approved
<b>ELECTRICAL CHARACTERISTICS (@ 1 KHz):</b>	Capacitance: 24 pF/ft nominal conductor to conductor. D.C. Resistance: 16.1 $\Omega$ /Kft nominal
<b>SURFACE PRINT:</b>	E111272 (01-12345) 22 AWG CL3P/FPLP (UL) OR CMP C(UL)US RoHS Sequential footage markers every 2 feet